

WP-306

Active Wall Plate - HDMI over Twisted Pair Transmitter















The WP-306 is a wall plate transmitter for HDMI signals. The unit converts the input signals to a DGKat[™] twisted pair signal that a compatible Kramer receiver converts back to the original signals.

FEATURES

- Max. Data Rate 4.95Gbps (1.65Gbps per graphic channel).
- Front Connections 1 HDMI & 1 3.5mm for IR (Compatible only with SV-552).
- Rear Connections 1 RJ-45 (US Version) or Terminal block (EU Version).
- HDCP Compliant.
- HDTV Compatible.
- DGKat[™] Signal Integration Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables. We strongly recommend using Kramer DGKat[™] cables designed specifically for optimum performance.
- EDID PassThru Passes EDID signals between the source and display.
- Power Connect™ System The SV-552 powers the unit via CAT 5 cable.
- Compatible Receivers PT-572+, TP-574, TP-575, TP-576.
- Dimensions 7.9cm x 2.9cm x 12.4cm (3.12" x 1.14" x 4.88") US; 8.6cm x 2.58cm x 8.6cm (3.39" x 1.01" x 3.39") and 8cm x 2.58cm x 8cm (3.15" x 1.01" x 3.15") EU W, D, H.
- Availability Available in white. US version includes a removable wall plate frame.
- Accessories Power supply.
- Optional RK-121WP 19" rack adapter (EU Version).

TECHNICAL SPECIFICATIONS