



## 482xl

### Balanced/Unbalanced Stereo Audio Transcoder

---



The **482xl** is a high-performance audio transcoder for balanced and unbalanced stereo audio signals. It simultaneously converts balanced stereo signals to unbalanced stereo audio and unbalanced stereo audio signals to balanced stereo audio.

### FEATURES

---

- **Bidirectional Format Conversion** - Balanced stereo audio to unbalanced stereo audio and unbalanced stereo audio to balanced stereo audio simultaneously.
- **Connectors** - Terminal blocks (balanced & unbalanced).
- **Level (Gain) Control** - Independent L & R adjustment while transcoding for both balanced to unbalanced conversion and unbalanced to balanced conversion.
- **S/N Ratio** - 95dB balanced to unbalanced, 87dB unbalanced to balanced, unweighted.
- **Compact Kramer TOOLS™** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

## TECHNICAL SPECIFICATIONS

INPUTS:	1 unbalanced audio stereo on a 3-pin terminal block connector, 1 balanced audio stereo on a 5-pin terminal block.
OUTPUTS:	1 balanced audio stereo on a 5-pin terminal block connector, 1 unbalanced audio stereo on a 3-pin terminal block connector.
MAX. OUTPUT LEVEL:	Balanced: 21dBu; unbalanced: 21dBu @max gain.
BANDWIDTH (-3DB):	>100kHz.
CONTROLS:	-57dB to +6dB (balanced to unbalanced level); -16dB to +19dB (unbalanced to balanced level).
COUPLING:	Balanced to unbalanced: in=AC, out=DC; Unbalanced to balanced: in=AC, out=DC.
THD+NOISE:	0.049%.
2ND HARMONIC:	0.005%.
S/N RATIO:	95dB/87dB balanced to unbalanced/unbalanced to balanced, unweighted.
POWER CONSUMPTION:	12V DC, 280mA (fully loaded).
INCLUDED ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.
PRODUCT DIMENSIONS:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.0kg (0.0lbs) approx.
SHIPPING DIMENSIONS:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx.

