



671R

4K60 4:2:0 DVI HDCP 2.2 over Ultra-Reach MM Fiber Optic Receiver



The **671R** is a high-performance fiber optic receiver for DVI signals. The unit receives an optical signal that is transmitted over one single fiber optic cable from the 671T and converts it back to a DVI signal.

FEATURES

- Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel).
- HDCP Compliant.
- HDTV Compatible.
- EDID PassThru - Passes EDID signals between the source and display.
- HDMI Support - Deep Color, x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD.
- 3D Pass-Through.
- Laser Standards Compliance - IEC 60825-1, FDA 21CFR1040; Laser Class 1: Safety of laser products.
- Output - DVI-D signal (on a DVI-I connector).
- System Range - 1700m (5570ft).
- Cable - Multimode fiber optic OM3 cable with SC connectors.
- Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	1 optical connector.
OUTPUTS:	DVI connector.
MAX. DATA RATE:	4.95Gbps (1.65Gbps per graphic channel).
EXTENSION LIMIT:	2000m (>6560 feet) for UXGA (1600x1200) and 1080p.
INSERTION LOSS FROM TRANSMITTER TO RECEIVER:	Must not exceed 10dB.
FIBER-OPTIC CONNECTION:	SC connectors for multimode (OM3) fiber cable.
INDICATOR LEDES:	Video, source, acceptor fiber and on LEDs.
POWER CONSUMPTION:	5V DC, 400mA.
INCLUDED ACCESSORIES:	2 power supplies (5V/2A), 2 bracket installation kits.
OPTIONS:	RK-3T 19" rack adapter. DVI/DVI male-to-male cable.
PRODUCT DIMENSIONS:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx.
SHIPPING DIMENSIONS:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx.

