



900N

Stereo Power Amplifier (10 Watts per Channel)



The **900N** is a high-performance power amplifier for balanced or unbalanced stereo audio signals. Either input can deliver a speaker output of 10 watts RMS power per channel into a 4Ω load.

FEATURES

- High Efficiency - Class D operation.
- S/N Ratio - 55dB.
- Controls - Volume knob, On LED.
- Special Note - Before turning on the 900N, make sure the volume is turned down to the minimum.
- Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	1 unbalanced stereo audio on RCA connectors; 1 balanced stereo audio on a 5-pin terminal block connector.
OUTPUT:	1 stereo loudspeaker output on a 4-pin terminal block connector.
OUTPUT POWER:	10W RMS per channel into a 4Ω load.
OUTPUT MUSIC POWER:	35W RMS per channel into a 4Ω load.
BANDWIDTH (-3DB):	24kHz.
S/N RATIO:	55dB.
CONTROLS:	Gain: -40dB to +19dB until the compression threshold.
COUPLING:	Input: AC; speakers out: DC.
AUDIO THD + NOISE:	0.5% @1kHz.
AUDIO 2ND HARMONIC:	0.04% @1kHz.
POWER CONSUMPTION:	12V DC, 2.1A.
INCLUDED ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.
PRODUCT DIMENSIONS:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx.
SHIPPING DIMENSIONS:	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H
SHIPPING WEIGHT:	0.6kg (1.3lbs) approx.

