



F670-IN4-F32

4-Channel HDMI over OM3 Fiber Input Card



F670-IN4-F32 is a four-channel HDMI over OM3 fiber input card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. The F670-IN4-F32 inputs four HDMI over OM3 fiber signals into the chassis.

FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDCP Compliant.
- 3D Pass-Through.
- Compatible with 670R/T.
- SC Fiber Connectors.

TECHNICAL SPECIFICATIONS

INPUTS	4 SC connectors.
BANDWIDTH PER CHANNEL:	2.25Gbps.
TOTAL BANDWIDTH:	6.75Gbps.
MAXIMUM RANGE:	1700m (5570ft) – 1080p/60Hz.
3D PASS THROUGH:	Supported.
POWER CONSUMPTION:	12W.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	–40° to +70°C (–40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
STANDARD COMPLIANCE:	HDCP 1.4, HDMI 1.3a.
SAFETY REGULATORY COMPLIANCE:	CE, FCC.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.