



## FC-332

3G HD-SDI to HDMI Format Converter

---



The **FC-332** is a high-performance format converter for video signals up to 3G HD-SDI. The unit converts the input video format (with embedded audio) to two HDMI outputs.

### FEATURES

---

- HDTV Compatible.
- Looping Input.
- Multi-Standard Operation - SDI (SMPTE 259M), HD-SDI (SMPTE 292M) and 3G HD-SDI (SMPTE 424M) compliance and support for data rates of 270Mbps, 1483.5Mbps, 1485Mbps and 2970Mbps.
- Embedded Audio Group Select Rotary Switch.
- Active Input Indication™ Reporting - Green indicates a standard definition (SDI) input signal and blue indicates a high definition (HD-SDI) input signal.
- Compact DigiTOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUT:	1 SD/HD/3G HD-SDI with loop on BNC connectors.
OUTPUTS:	2 HDMI connectors.
MAX. DATA RATE:	Up to 3Gbps.
STANDARD COMPLIANCE:	HDMI.
INDICATOR LEDES:	SD/HD, OUT, ON.
POWER CONSUMPTION:	5V DC, 510mA.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-3T 19" rack adapter.
PRODUCT DIMENSIONS:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.3kg (0.7lbs) approx.
SHIPPING DIMENSIONS:	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50" ) W, D, H
SHIPPING WEIGHT:	0.6kg (1.3lbs) approx.

