



## HAA-OUT2-F16

2-Channel HDMI with Analog Audio Output Card

---



HAA-OUT2-F16 is a two-channel HDMI with analog audio output card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The HAA-OUT2-F16 outputs two HDMI signals with de-embedded unbalanced stereo audio from the chassis.

### FEATURES

---

- Analog Audio Embedding/De-embedding.
- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDCP Compliant.
- HDMI Support.
- 3D Pass-Through.

## TECHNICAL SPECIFICATIONS

---

PORTS:	2 HDMI, 2 analog audio on 3.5mm mini jacks.
BANDWIDTH PER CHANNEL:	2.25Gbps.
TOTAL BANDWIDTH:	6.75Gbps.
MAXIMUM RANGE:	15m (49ft).
3D PASS THROUGH:	Supported.
POWER CONSUMPTION:	7W.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	19cm x 13cm x 2cm (7.5" x 5.1" x 0.8") W, D, H.
PRODUCT WEIGHT:	0.23kg (0.51lbs) approx.
SHIPPING WEIGHT:	0.37kg (0.82lbs) approx.
STANDARD COMPLIANCE:	HDCP 1.4, HDMI 1.3a.
SAFETY REGULATORY COMPLIANCE:	CE.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.