



HAA-OUT4-F32

4-Channel HDMI with Analog Audio Output Card



HAA-OUT4-F32 is a four-channel HDMI with analog audio output card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. The HAA-OUT4-F32 outputs four HDMI signals with de-embedded unbalanced stereo audio from the chassis.

FEATURES

- Analog Audio Embedding/De-embedding.
- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDCP Compliant.
- HDMI Support.
- 3D Pass-Through.

TECHNICAL SPECIFICATIONS

OUTPUTS	4 HDMI, 4 analog audio on 3.5mm mini jacks.
BANDWIDTH PER CHANNEL:	2.25Gbps.
TOTAL BANDWIDTH:	6.75Gbps.
MAXIMUM RANGE:	15m (49ft).
3D PASS THROUGH:	Supported.
POWER CONSUMPTION:	12W.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
STANDARD COMPLIANCE:	HDCP 1.4, HDMI 1.3a.
SAFETY REGULATORY COMPLIANCE:	CE.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.