



## HAD-OUT4-F32

4-Channel HDMI with Digital Audio Output Card

---



HAD-OUT4-F32 is a four-channel HDMI with digital audio output card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. The HAD-OUT4-F32 outputs four HDMI signals with de-embedded S/PDIF audio from the chassis.

### FEATURES

---

- Digital Audio Embedding/De-embedding.
- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDCP Compliant.
- HDMI Support.
- 3D Pass-Through.

## TECHNICAL SPECIFICATIONS

---

OUTPUTS	4 HDMI, 4 digital audio on RCA connectors.
BANDWIDTH PER CHANNEL:	2.25Gbps.
TOTAL BANDWIDTH:	6.75Gbps.
3D PASS THROUGH:	Supported.
POWER CONSUMPTION:	9W.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
STANDARD COMPLIANCE:	HDCP 1.4, HDMI 1.3a.
SAFETY REGULATORY COMPLIANCE:	CE.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.
PRODUCT DIMENSIONS:	22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79" ) W, D, H
PRODUCT WEIGHT:	0.3kg (0.7lbs) approx.
SHIPPING DIMENSIONS:	25.00cm x 22.50cm x 5.50cm (9.84" x 8.86" x 2.17" ) W, D, H
SHIPPING WEIGHT:	0.5kg (1.0lbs) approx.