



HDCP-IN4-F32

4-Channel DVI (HDCP) Input Card



HDCP-IN4-F32 is a four-channel HDMI over DVI (HDCP) input card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. The HDCP-IN4-F32 inputs four HDMI/HDCP signals into the chassis.

FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDCP Compliant.
- HDMI Support.
- 3D Pass-Through.
- DVI Connectors.

TECHNICAL SPECIFICATIONS

INPUTS:	4 DVI-D on DVI Molex 24-pin (F) connectors.
BANDWIDTH PER CHANNEL:	2.25Gbps.
TOTAL BANDWIDTH:	6.75Gbps.
3D PASS THROUGH:	Supported.
POWER CONSUMPTION:	9W.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
STANDARD COMPLIANCE:	HDCP, HDMI.
SAFETY REGULATORY COMPLIANCE:	CE, FCC.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.