



HH-IN2-F16

2-Channel HDMI Input Card



HH-IN2-F16 is a two-channel HDMI input card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The HH-IN2-F16 inputs two HDMI signals into the chassis.

FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDCP 1.4 Compliant.
- HDMI 1.3a Compliant.
- 3D Pass-Through.

TECHNICAL SPECIFICATIONS

PORTS:	2 HDMI.
BANDWIDTH PER CHANNEL:	2.25Gbps.
TOTAL BANDWIDTH:	6.75Gbps.
MAXIMUM RANGE:	15m (49ft).
3D PASS THROUGH:	Supported.
POWER CONSUMPTION:	5W.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F) .
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	19cm x 13cm x 2cm (7.5" x 5.1" x 0.8") W, D, H.
PRODUCT WEIGHT:	0.23kg (0.51lbs) approx.
SHIPPING WEIGHT:	0.37kg (0.82lbs) approx.
STANDARD COMPLIANCE:	HDCP 1.4, HDMI 1.3a.
SAFETY REGULATORY COMPLIANCE:	CE.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.