



K304E

HighSecLabs Secure 4-Port KM Switch



The **K304E** is a secure 4-port KM Switch. It allows an easy yet secure sharing of keyboard and mouse between four different security-level sources/computers. **K304E** provides the highest possible isolation between four connected computers.

HSL Virtual Display Technology (VDT) switches the **K304E** seamlessly between computers once the mouse cursor crosses display borders. The **K304E** works smoothly with all operating systems, from Microsoft to Linux and Apple with no need for software installation. For enhanced security, a USB user authentication port (DPP) connects to a smart card or biometric reader. This requires the insertion of a physical authentication card or identification of a fingerprint to access the various computers/networks.

FEATURES

- **Virtual Display Technology (VDT)** - Seamless keyboard, mouse and audio switching between computers once mouse cursor crosses display borders.
- **Display Configurations** - Arrives with a predefined preset of display configurations for ease of use. In addition, HSL VDT application allows administrators to configure any desired display configuration required.
- **Multiple-Head Support** - Can be easily configured to support dual/triple/multiple displays through HSL VDT application.
- **OS Independent** - Support for all Microsoft OS, Linux and Apple with no need for SW installation
- **Biometric/Smart-Card Reader Support** - Special secured port (DPP) for smart-card/biometric reader with patented freeze function to support user authentication across multiple isolated networks.
- **Highest Security by Design** - Common Criteria EAL 4+ approved, compatible with NIAP security requirements.
- **Hardware-Based Peripheral Isolation** - No dependency on firmware or software, all firmware on ROM (Read Only Memory), no keyboard buffering or memory.
- **Unidirectional Optical Data Diodes** - Assures USB peripheral isolation, data flows from devices to host only.
- **Peripheral Security** - Full USB device filtering to assure support for keyboard and mouse only.
- **Active Anti-Tampering System** - Always-on with 10 years battery, holographic tampering evident labels.

TECHNICAL SPECIFICATIONS

HOST INPUT PORTS:	4 USB-B connector for keyboard and mouse, 4 3.5mm mini jack for unbalanced stereo audio, 4 USB-B dedicated peripheral ports (DPP).
CONSOLE PORTS:	2 USB-A connectors for keyboard and mouse, 1 USB-A dedicated peripheral port (DPP), 2 DIN-5 connectors for PS/2 keyboard and mouse, 1 3.5mm mini jack for unbalanced stereo audio.
CHANNEL SWITCHING:	Front panel buttons.
POWER CONSUMPTION:	12V DC, 1.5A max.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +60°C (-40° to 140°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
SECURITY ACCREDITATIONS:	Common Criteria EAL 4+ ALC_FLR.3.
INCLUDED ACCESSORIES:	Power supply.