



PSE-4

Quad 10G HDBaseT & Ethernet Power Injector



The PSE-4 is a four-way PoE (Power-over-Ethernet) injector that supports 4K UHD video. The unit provides power remotely over Ethernet to up to four devices capable of acting as PoE acceptors, (for example, the DIP-20, where it might be difficult to connect an external power supply). This allows a single HDBT LAN cable to provide both data and electrical power to compatible devices.

FEATURES

- 4K Support.
- 48V DC Power.
- Total Range - up to 100m (328ft) @4K on shielded BC-HDKat6a cable (or equivalent).

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------------|---|
| INPUT/OUTPUT: | 4 HDBaseT/LAN on RJ-45 connectors, 4 HDBaseT/LAN + PoE on RJ-45 connectors. |
| OPERATION BANDWIDTH: | Up to 10.2Gbps (3.4Gbps per data channel). |
| COMPLIANCE WITH HDMI STANDARD: | Supports HDMI, HDCP. |
| INDICATOR LEDS: | ON, PoE STATUS. |
| POWER CONSUMPTION: | 48V DC, 2.5A. |
| POWER PROVISION: | Up to 30W per output (120W total). |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F). |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F). |
| HUMIDITY: | 10% to 90%, RHL non-condensing. |
| COOLING: | Convection, vents. |
| ENCLOSURE TYPE: | Aluminum. |
| RACK MOUNT: | With optional adapter. |
| FURNITURE MOUNT: | With included rubber feet. |
| VIBRATION: | ISTA 1A in carton (International Safe Transit Association). |
| SAFETY REGULATORY COMPLIANCE: | CE. |
| ENVIRONMENTAL REGULATORY COMPLIANCE: | Complies with appropriate requirements of RoHs and WEEE. |
| INCLUDED ACCESSORIES: | Power supply. |
| OPTIONS: | RK-4PT 19" rack adapter. |
| WARRANTY: | 7 years parts and labor. |
| PRODUCT DIMENSIONS: | 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H |
| PRODUCT WEIGHT: | 0.4kg (1.0lbs) approx. |
| SHIPPING DIMENSIONS: | 17.40cm x 12.00cm x 8.60cm (6.85" x 4.72" x 3.39") W, D, H |
| SHIPPING WEIGHT: | 1.3kg (2.9lbs) approx. |

