



PT-102AN

1:2 Stereo Audio Distribution Amplifier



The **PT-102AN** is a high-performance audio distribution amplifier for unbalanced stereo signals. The unit takes one stereo input and distributes the signal to two identical stereo outputs.

FEATURES

- Level (Gain) Controls.
- S/N Ratio - 85dB.
- Ultra-Compact Pico TOOLS™ - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter.

TECHNICAL SPECIFICATIONS

INPUT:	1 unbalanced stereo audio on a 3.5mm mini jack.
OUTPUTS:	2 unbalanced stereo audio on 3.5mm mini jacks.
MAX. OUTPUT LEVEL:	5Vpp.
BANDWIDTH (-3DB):	>100kHz.
S/N RATIO:	85dB @1kHz.
CONTROLS:	Level: -55dB to +20dB.
COUPLING:	AC.
AUDIO THD + NOISE:	0.01% @1kHz.
AUDIO 2ND HARMONIC:	0.004% @1kHz.
POWER CONSUMPTION:	12V DC, 20mA.
INCLUDED ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-4PT 19" rack adapter.
PRODUCT DIMENSIONS:	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H
PRODUCT WEIGHT:	0.1kg (0.2lbs) approx.
SHIPPING DIMENSIONS:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.4kg (0.8lbs) approx.

