




## PT-110xl

Computer Graphics Video over Twisted Pair Transmitter with EDID

---



The **PT-110xl** is an extended range UXGA line transmitter that receives a UXGA signal and transmits it over a CAT 5/6 cable to the PT-120xl or TP-120 receiver.

### FEATURES

---

- Resolution - Up to WUXGA & 1080p.
- HDTV Compatible.
- Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other.
- Extended Transmission Range - Up to 250m (820ft) when used with Kramer's twisted pair xl receivers (such as PT-120xl, TP-122xl or TP-126xl).
- EDID Capture - Copies and stores the EDID from a display device.
- Increased Noise Immunity - An increased level of protection against noise, spikes and interference in adverse environments.

TECHNICAL SPECIFICATIONS

INPUT:	1 VGA/UXGA on a 15-pin HD connector.
OUTPUT:	1 twisted pair on an RJ-45 connector.
RESOLUTION:	Up to WUXGA, 1080p.
RANGE:	Up to 250m (820ft).
S/N RATIO:	Paired with PT-120xl, better than 70dB (worst case).
COUPLING:	AC.
POWER CONSUMPTION:	12V DC, 285mA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-4PT 19" rack adapter.
PRODUCT DIMENSIONS:	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.1kg (0.2lbs) approx.
SHIPPING DIMENSIONS:	17.40cm x 12.00cm x 8.60cm (6.85" x 4.72" x 3.39" ) W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx.

