



PT-2SPDIF

TOSLINK® to S/PDIF Digital Audio Format Converter



The **PT-2SPDIF** is a format converter for TOSLINK® digital audio signals. It converts a TOSLINK® optical signal to a S/PDIF signal.

FEATURES

- TOSLINK® Input - TOSLINK® Connector.
- S/PDIF Output - RCA Connector.
- Compact Size - Part of the Kramer TOOLS™ family of compact, high quality and cost effective solutions.

TECHNICAL SPECIFICATIONS

INPUT:	1 optical (digital audio) on a TOSLINK® connector.
OUTPUT:	1 S/PDIF (digital audio) on an RCA connector.
SAMPLING:	32kHz to 192kHz.
POWER CONSUMPTION:	12V DC, 50mA.
INCLUDED ACCESSORIES:	Power supply.
PRODUCT DIMENSIONS:	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H
PRODUCT WEIGHT:	0.1kg (0.1lbs) approx.
SHIPPING DIMENSIONS:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.3kg (0.7lbs) approx.

