



## PT-4iREX

IR Repeater with External IR Sensor Input

---



The PT-4iREX is an infrared signal repeater that operates at distances of up to approximately 75m (240ft). It extends infrared signals in areas where there is no direct line-of-sight for normal infrared signal operation.

### FEATURES

---

- **Input** - Built-in IR receiver and 3.5mm connector for external IR receiver at cable distances up to about 30m (100ft).
- **Outputs** - 4 outputs control up to 8 IR devices at cable distances up to approximately 75m (240ft).
- **Signal Application** - For use with all wireless IR signals (not hard-wired IR signals).
- **Ultra-Compact Pico TOOLS™** - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter.

TECHNICAL SPECIFICATIONS

INPUT:	1 IR receiver.
OUTPUTS:	4 IR emitters on 3.5mm mini connectors.
IR OPERATING FREQUENCY:	38kHz +/-10%.
EFFECTIVE OFF-AXIS ANGLE:	120° max.
POWER CONSUMPTION:	12V DC, 95mA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
INCLUDED ACCESSORIES:	Power supply; 3.5mm to IR emitter control cable (C-A35/IRE-10); 0.9m external remote IR receiver.
OPTIONS:	RK-4PT 19" rack adapter; external IR receiver cables: C-A35M/IRR-3 and C-A35M/IRR-50; IR emitter cable: C-A35/2IRE-10 dual emitter.
PRODUCT DIMENSIONS:	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.1kg (0.1lbs) approx.
SHIPPING DIMENSIONS:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43" ) W, D, H
SHIPPING WEIGHT:	0.4kg (0.9lbs) approx.

