



RB-6

6-Channel Power Controller



The RB-6 is a high-performance power supply that distributes power to up to six external units. Four power outlets have on/off push-button control and two power outlets have on/off switching as well as full voltage control.

FEATURES

- **Active Output Control** - All outputs On/Off control, 5 & 6 min/max with full voltage variability via rotary knobs.
- **Power Output** - 10A total, maximum 6A per output.
- **Embedded Web Server Control** - Turns On & Off all channels and adjusts voltage on 5 & 6, schedules outlet activity of each channel separately via Ethernet.
- **Expandable** - Cascades up to 8 units.
- **Varied Control Options** - Front panel buttons, IR remote control, RS-232, RS-485 & Ethernet.
- **Indicators** - Push button LEDs show active output, power and IR status LEDs.
- **Worldwide Power Supply** - 100-240V AC, US and EU models available.
- **Standard 19" Rack Mount Size** - 1U. Rack "ears" included.

TECHNICAL SPECIFICATIONS

INPUT:	1 AC power input.
OUTPUTS:	6 controllable AC power outputs.
CONTROL:	Front panel buttons, IR remote control, RS-232 on a 9-pin D-sub connector, RS-485 on a 3-pin terminal block, Ethernet on an RJ-45 connector, embedded Web server.
POWER CONSUMPTION:	100-240V AC, 50/60Hz, 30VA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
INCLUDED ACCESSORIES:	Rack "ears", IR remote control, power cord.
OPTIONS:	Remote IR receiver cable Kramer P/N 505-70434010-S.
PRODUCT DIMENSIONS:	19" x 9.34 x 1U (43.6cm x 23.72cm 4.36cm) W, D, H
PRODUCT WEIGHT:	2.2kg (4.9lbs) approx.
SHIPPING DIMENSIONS:	52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H
SHIPPING WEIGHT:	3.3kg (7.2lbs) approx.

