



RC-43T

6-button Touch-sensitive KNET™ Auxiliary Keypad (US)



The RC-43T is a touch-sensitive 6-button auxiliary keypad. Connected over KNET™ to master control keypad such as RC-43SL, RC-74DL, or SL-1N, the RC-43T is ideal for serving as remote secondary keypad in classrooms, boardrooms or auditoriums, for convenient control of their multimedia devices.

FEATURES

- **Touch-sensitive & Label Capable Buttons** - 6 white-color LED-feedback buttons.
- **Custom Labeled, Removable Button Caps.**
- **1 K-NET™ Connector** - Connect to master room controller, and auxiliary keypads for remote keypad control.
- **K-NET™ Single Link Connection** - Provides a single keypad link cable-connectivity, carrying both power and keypad control.
- **Program Control** - Program configuration with Kramer K-Config software.
- **Mini USB Port** - To upload configuration files, set the K-NET™ ID number, and power the device during configuration.
- **Mounting** - In-wall, in standard 1 gang US wall junction boxes.
- **Easy Installation** - Fits to standard in-wall boxes for simple and cost-reducing installation.

TECHNICAL SPECIFICATIONS

PORT:	1 K-NET on a 4-pin removable terminal block.
POWER CONSUMPTION:	12V DC, 100mA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
INCLUDED ACCESSORIES:	Power supply, labeled caps set, screwdriver.
PRODUCT DIMENSIONS:	6.90cm x 0.00cm x 11.43cm (2.72" x 0.00" x 4.50") W, D, H
PRODUCT WEIGHT:	0.1kg (0.1lbs) approx.
SHIPPING DIMENSIONS:	25.60cm x 11.80cm x 11.40cm (10.08" x 4.65" x 4.49") W, D, H
SHIPPING WEIGHT:	0.0kg (0.0lbs) approx.

CONFIGURATIONS

RC-43T/US	US-size RC-43T, White + Black Design Frames, PSU + Power cord, Labeled Caps Set, Screwdriver
RC-43T/JP	US-size RC-43T, White + Black Design Frames, PSU + Japan Power cord, Labeled Caps Set, Screwdriver

