




RC-712M

12-button Ethernet and KNET™ Control Keypad (UK-Merten)



The RC-712M is a 12-button control keypad that fits into standard Merten on-wall boxes. Connected over Ethernet to Site-CTRL™ remote AV control, site management & monitoring system, as well as LAN-connected control gateways for extended controlled devices capacity, and over KNET™ to master room controller and auxiliary keypads for remote keypad control, it can flexibly serve either as a standalone room controller, part of multi-units KNET™ system, or part of multi-unit Ethernet system managed by Kramer Site-CTRL™ site management platform. The RC-712M is ideal for auditoriums and meeting rooms, for convenient control of their complex multimedia systems and other room facilities such as screens, lighting and shades.

FEATURES

- Back Lit & Label Capable Buttons - 12 RGB-color, tactile feedback, backlit buttons grouped in two groups.
- Custom Labeled, Removable Button Caps.
- 1 K-NET™ Connector - Connect to master room controller, and auxiliary keypads for remote keypad control.
- K-NET™ Single Link Connection - Provides a single keypad link cable-connectivity, carrying both power and keypad control communication information.
- 1 RS-485 Bi-directional Control Port - Control devices via RS-485 control protocols.
- 2 RS-232 Bi-directional Control Ports - Control a device via bi-directional serial control protocols.
- 2 IR Emitter Control Ports - Control a device via IR control protocols.
- 1 GPI/O Control Port - Controls a device via general purpose I/O ports, program-configured as digital input, digital output or analog input interface for controlling sensors, door-locks, audio volume and light dim level, or lighting control devices.
- 2 Relay Control Ports - Control a device via relay contact closure, such as scrolling up and down screens, drapes, shades, and blinds.
- IR Sensor Port - Learns commands from IR remotes.
- Program Control - Program configuration with Kramer K-Config software.
- Kramer Site-CTRL™ Compatibility - For network management and remote control over the Ethernet port.
- Keypad Lock-Out - Option for tampering prevention by locking and unlocking of the keypad buttons.
- Mini USB Port - To upload configuration files, set the K-NET™ ID number, and power the device during configuration.
- Mounting - On-wall, in standard 2 gang UK Merten System M boxes.
- Easy Installation - Fits to standard on-wall boxes for simple and cost-reducing installation.

TECHNICAL SPECIFICATIONS

INPUTS:	1 RS-485, 2 RS-232, 1 GPI/O, 1 K-NET on terminal block connectors, 1 Ethernet on an RJ-45 connector, 1 infrared sensor , 1 mini USB for programming.
OUTPUTS:	2 IR emitter, 2 relays (36V AC or DC, 2A, 60V AC maximum on non-inductive load) on terminal block connectors.
DEFAULT IP SETTINGS:	IP number – 192.168.1.39; Mask – 255.255.0.0; Gateway – 0.0.0.0.
POWER CONSUMPTION:	12V DC, 460mA (full load).
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
INCLUDED ACCESSORIES:	Power supply, white design plate, label set, screwdriver, L-key hex socket.
PRODUCT DIMENSIONS:	13.97cm x 2.31cm x 6.86cm (5.50" x 0.91" x 2.70") W, D, H
PRODUCT WEIGHT:	0.1kg (0.2lbs) approx.
SHIPPING DIMENSIONS:	25.60cm x 11.80cm x 11.40cm (10.08" x 4.65" x 4.49") W, D, H
SHIPPING WEIGHT:	0.5kg (1.0lbs) approx.

CONFIGURATIONS

RC-712M/EU	UK-Merten-size RC-712M, White design plate, PSU + Power cord, L-key hex socket, Label Set
RC-712M/JP	UK-Merten-size RC-712M, White design plate, PSU + Japan Power cord, L-key hex socket, Label Set
RC-712M/JP	UK-Merten-size RC-712M, White design plate, PSU + Japan Power cord, L-key hex socket, Label Set
RC-712M/JP	UK-Merten-size RC-712M, White design plate, PSU + Japan Power cord, L-key hex socket, Label Set
RC-712M/JP	UK-Merten-size RC-712M, White design plate, PSU + Japan Power cord, L-key hex socket, Label Set
RC-712M/JP	UK-Merten-size RC-712M, White design plate, PSU + Japan Power cord, L-key hex socket, Label Set
RC-712M/JP	UK-Merten-size RC-712M, White design plate, PSU + Japan Power cord, L-key hex socket, Label Set

