



TBUS-1Axl

Table Mount Modular Multi-Connection Solution – Tilt-Up Lid



The TBUS-1Axl is the enclosure of a new modular system with a tilt-up lid. A complete TBUS system requires the enclosure, an inner frame, a power socket, inserts and a power cord.

NOTE: The TBUS enclosure, power socket, power cord & inserts are purchased separately.

Photos Above Show A Fully Populated TBUS-1Axl

FEATURES

- **Cover** - Manually opens & closes.
- **Inner Frame** - 6 different "TIAF" inner frame options are available that can accommodate a combination of up to 4 power sockets, 6 cable pass-through or connector inserts, 1 long insert and up to 3 Kramer TOOLS.
- **Power Sockets** - 8 different "TS" single and 8 dual power socket options are available to accommodate the power requirements worldwide.
- **Power Cord** - 8 different "C-AC" single power cords (and 3 "Y" power cords) for each power socket.
- **Optional Accessories** - TBUS Brackets, K-Able Box Cable Reels, Step-In Modules and Controllers are available.
- UL and CE Qualified.
- **Connector Depth** - Adjustable.
- **Installation Requirement** - Table cutout of 19.1cm x 15.2cm (7.51in x 5.98in).
- **Dimensions** - 20.5cm x 17cm x 13.2cm (8.1" x 6.7" x 5.2") W, D, H.
- **Weight** - TBUS-1Axl: 1.5kg (3.3lbs) approx.; table clamps: 0.26kg (0.57lbs); metal template: 0.125kg (0.28lbs).