



## TP-104HD

1:4 Computer Graphics Video & HDTV over Twisted Pair Transmitter & Distribution Amplifier

---



The **TP-104HD** is a twisted pair transmitter for computer graphics video and HDTV signals. It converts a computer graphics video or HDTV signal on a 15-pin HD connector to four identical twisted pair signals.

## FEATURES

---

- HDTV Compatible.
- Max. Resolution - WUXGA & 1080p.
- **Power Connect™ System** - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other.
- **Cable** - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5.
- **System Range** - Up to 100m (320ft).
- **Compact Kramer TOOLS™** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUT:	1 UXGA on a 15-pin HD connector.
OUTPUTS:	4 twisted pair on RJ-45 connectors.
MAX. OUTPUT LEVEL:	1.4Vpp.
MAX. RESOLUTION:	WUXGA & 1080p.
DIFF. GAIN:	3.2%.
DIFF. PHASE:	0.5Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	80dB.
COUPLING:	AC.
POWER CONSUMPTION:	12V DC, 180mA.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-3T 19" rack adapter.
PRODUCT DIMENSIONS:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx.
SHIPPING DIMENSIONS:	0.00cm x 0.00cm x 0.00cm (0.00" x 0.00" x 0.00" ) W, D, H
SHIPPING WEIGHT:	0.6kg (1.3lbs) approx.

