



TP-42

Component Video & S/PDIF Audio over Twisted Pair Receiver



The TP-42 is a twisted pair receiver for component video (YUV) and S/PDIF audio signals. The TP-41 transmitter converts component video (YUV) and S/PDIF audio signals into a twisted pair signal and the TP-42 converts the twisted pair signal back into component video (YUV) and S/PDIF audio signals.

FEATURES

- HDTV Compatible.
- Max. Resolution - 1080i.
- Level (Gain) and EQ (Peaking) Controls.
- System Range - Up to 100m (320ft).
- Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5.

TECHNICAL SPECIFICATIONS

INPUT:	1 RJ-45 CAT 5 shielded connector (line in).
OUTPUTS:	1 set of component video (Y, U, V) on RCA connectors; 1 S/PDIF (digital audio) on an RCA connector.
MAX. OUTPUT LEVEL:	Video: 2.1Vpp.
MAX. RESOLUTION:	1080i.
DIFF. GAIN:	0.15%.
DIFF. PHASE:	0.68Deg.
K-FACTOR:	0.8%.
S/N RATIO:	Video: 78dB; Audio: 78.4dB.
CROSSTALK (ALL HOSTILE):	Video: -55dB; Audio: -50.5dB.
CONTROLS:	YUV level: -0.7dB to +0.8dB; YUV equalization: 0 to +7.5dB; S/PDIF level: -0.5dB to +1.2dB; S/PDIF equalization: 0 to +7.8dB.
COUPLING:	DC.
POWER CONSUMPTION:	12V DC, 82mA.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-3T 19" rack adapter.
PRODUCT DIMENSIONS:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx.
SHIPPING DIMENSIONS:	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx.

