



TP-573

HDMI HDCP 2.2 Transmitter with RS-232 & IR over PoC Long-Reach DGKat



The TP-573 is a DGKat™ twisted pair transmitter for HDMI, bidirectional RS-232 and infrared signals. The TP-573 converts the input signals to a twisted pair signal and the TP-574 converts it back to HDMI, RS-232 and infrared signals.

FEATURES

- **Max. Data Rate** - 4.95Gbps (1.65Gbps per graphic channel).
- **HDTV Compatible.**
- **HDCP Compliant.**
- **DGKat™ Signal Integration** - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables.
- **HDMI Support** - x.v.Color™, Lip Sync, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD.
- **3D Pass-Through.**
- **EDID PassThru** - Passes EDID signals between the source and display.
- **Bidirectional RS-232 & IR Interface.** - 38400 max baud rate.
- **System Range** - Up to 90m (295ft) at 1080i, or up to 30m (98ft) at 1080p on shielded BC-DGKat524 cable. Up to 90m (295ft) at 1080i, or up to 70m (230ft) at 1080p on shielded BC-DGKat623 cable. Up to 100m (330ft) at 1080i or up to 90m (295ft) at 1080p on shielded BC-DGKat723 cable.
- **Cable** - Requires shielded twisted pair (STP) cable. For optimum range and performance use, use Kramer's BC-DGKat524, BC-DGKat623 and BC-DGKat723 cables. Note that the transmission range depends on the signal resolution, graphics card and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.
- **Power Connect System™** - A single connection to the transmitter powers both units.
- **Compact DigiTOOLS®** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	1 HDMI connector, 1 bidirectional IR port on a 3.5mm mini jack, 1 bidirectional RS-232 port on a 9-pin D-sub connector.
OUTPUTS:	1 CAT 5 OUT on an RJ-45 connector.
BANDWIDTH:	4.95Gbps (1.65Gbps per graphic channel).
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
POWER CONSUMPTION:	12V DC, 510mA.
INCLUDED ACCESSORIES:	12V DC power supply.
OPTIONS:	RK-3T 19" rack mount, Kramer remote external receiver, Kramer BC DGKat524 (CAT 5 24AWG) and BC DGKat623 (CAT 6 23AWG) cables.
PRODUCT DIMENSIONS:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx.
SHIPPING DIMENSIONS:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx.

