



## TR-2A

Balanced Stereo Audio Isolation Transformer

---



The **TR-2A** is a high-performance isolation transformer for balanced stereo audio signals. It completely isolates devices to eliminate hum, ground loops, and DC offsets that can degrade audio quality.

### FEATURES

---

- S/N Ratio -  $-83\text{dB}$  @  $+4\text{dBu}$ , 1kHz.
- External Input & Output Ground Terminals.
- Grounding Options - DIP-switch selectable.
- Passive - No power required.
- Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3TR rack adapter.

## TECHNICAL SPECIFICATIONS

INPUT:	1 balanced stereo audio, +4dBu/600Ω on detachable terminal block.
OUTPUT:	1 balanced stereo audio, +4dBu/600Ω on detachable terminal block.
MAX. OUTPUT LEVEL:	+26dBu.
BANDWIDTH (-3DB):	20Hz to 20kHz.
S/N RATIO:	-83dBu @ +4dBu/1000Hz.
CONTROLS:	DIP-switches to connect to chassis.
COUPLING:	Transformer.
AUDIO THD + NOISE:	0.025% @ +4dBu/1000Hz.
INCLUDED ACCESSORIES:	Mounting brackets.
OPTIONS:	RK-3TR 19" rack adapter.
PRODUCT DIMENSIONS:	12.12cm x 7.23cm x 3.07cm (4.77" x 2.85" x 1.21" ) W, D, H
PRODUCT WEIGHT:	0.3kg (0.6lbs) approx.
SHIPPING DIMENSIONS:	23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94" ) W, D, H
SHIPPING WEIGHT:	0.5kg (1.2lbs) approx.

