



TR-94

Dual Audio Transformer



The TR-94 is a 2x200W transformer for speaker signals. The unit takes two 4Ω/8Ω channels from a speaker output of a power amplifier, transforms them to 70/100V and distributes them to an array of loudspeakers.

FEATURES

- Bandwidth - 18kHz (-3dB).
- Max. Power - 2x200 watts.
- Passive Device - No power required.

TECHNICAL SPECIFICATIONS

| | |
|------------------------|--|
| INPUTS: | 2 low-impedance ($4\Omega/8\Omega$) speaker inputs on terminal block connectors. |
| OUTPUTS: | 2 high-impedance speakers on terminal block connectors. |
| MAX POWER: | 2x200W. |
| VOLTAGE GAIN: | 7.4dB/10.5dB (70V/100V). |
| BANDWIDTH (-3dB): | 18kHz. |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F). |
| STORAGE TEMPERATURE: | -10° to +60°C (14° to 140°F). |
| HUMIDITY: | 10% to 90%, RHL non-condensing. |
| DIMENSIONS | 48.2cm x 17.7cm x 4.3cm (19" x 7" x 1.7") W, D, H. |
| WEIGHT: | 6.25kg (13.8lbs). |
| INCLUDED ACCESSORIES: | Rack "ears". |

