



VCO-1

Single Port HDMI Video Content Overlay Solution



The VCO-1 is a video content overlay solution that overlays one independent graphic image to any number of displays over standard HDMI in full HD – 1080p/60 or 1920x1200 resolution. This allows the display of individual, targeted messages for each and every display in your installation.

FEATURES

- Full HD Overlays - Static or animated, dynamic color image.
- Overlays Any Size Content with Full Transparency Control.
- Multiple Overlay Templates - For multiple applications.
- Built-in Looping Output - For daisy chaining any number of displays.
- Centralized Control of all Promotional Overlays.
- Support for Unlimited Number of Overlays and Displays.
- Error Reporting - Comprehensive error reporting for connected displays and overlays.
- Full Overlay Automation - Automates entire overlay process from design to display, in multiple locations.
- Easy to Use - Feature-rich software – design, schedule, and display.
- Enables Digital Signage with Unlimited Viewing Zones.

TECHNICAL SPECIFICATIONS

INPUTS:	1 HDMI connector (HDMI, HDCP version 1.4), 1 USB port.
OUTPUTS:	1 HDMI connector (HDMI, HDCP version 1.4).
PORTS:	1 RJ-45 Ethernet port 10/100BaseT.
BANDWIDTH:	Full HD resolution (1080p60 or 1920x1200).
CONTROLS:	IP address setup DIP-switches, Reset/Test button, Ethernet (VCO Setup App), output status indication LEDs, input indication LED.
POWER CONSUMPTION:	5V DC, 800mA max.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
PRODUCT DIMENSIONS:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.3kg (0.6lbs) approx.
SHIPPING DIMENSIONS:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.7kg (1.5lbs) approx.
INCLUDED ACCESSORIES:	Power supply unit (5V DC, 4A).

