



KRAMER

VGA-IN2-F16

2-Channel VGA Input Card



VGA-IN2-F16 is a two-channel VGA input card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The VGA-IN2-F16 inputs two VGA signals into the chassis.

FEATURES

- Max bandwidth - 450MHz.
- Auto or User-Defined Resolution Detection & Phase Mode.
- Adjustable Brightness & Contrast.

TECHNICAL SPECIFICATIONS

PORTS:	2 VGA on 15-pin HD connectors.
BANDWIDTH:	450MHz.
MAXIMUM RANGE:	10m (32ft).
POWER CONSUMPTION:	5.5W.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	19cm x 13cm x 2cm (7.5" x 5.1" x 0.8") W, D, H.
PRODUCT WEIGHT:	0.23kg (0.51 bs) approx.
SHIPPING WEIGHT:	0.37kg (0.82lbs) approx.
SAFETY REGULATORY COMPLIANCE:	CE.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.