



VGAA-IN2-F16

2-Channel VGA with Analog Audio Input Card



VGAA-IN2-F16 is a two-channel VGA with analog audio input card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The VGAA-IN2-F16 inputs two VGA with analog audio signals into the chassis. Audio is accessed by connecting the supplied Kramer VGA with audio cables to each VGA port.

FEATURES

- Max. Bandwidth - 450MHz.
- HDTV Compatible.
- Analog Audio Over Breakaway Connector.

TECHNICAL SPECIFICATIONS

PORTS:	2 VGA on 15-pin HD connectors, 2 unbalanced analog audio on 3.5mm mini jack connectors (accessible via C GF/GMAF-30 cables).
BANDWIDTH:	450MHz.
MAXIMUM RANGE:	10m (32ft).
POWER CONSUMPTION:	9.5W.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F) .
HUMIDITY:	10% to 90%, RHL non-condensing.
PRODUCT DIMENSIONS:	19.00cm x 13.00cm x 2.00cm (7.48" x 5.12" x 0.79") W, D, H
PRODUCT WEIGHT:	0.1kg (0.3lbs) approx.
SHIPPING DIMENSIONS:	27.00cm x 23.20cm x 5.60cm (10.63" x 9.13" x 2.20") W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx.
SAFETY REGULATORY COMPLIANCE:	CE.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.
INCLUDED ACCESSORIES:	2 C-GF/GMAF-30 cables.