



VGAA-OUT2-F16

2-Channel VGA with Analog Audio Output Card



VGAA-OUT2-F16 is a two-channel VGA with analog audio output card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The VGAA-OUT2-F16 outputs two VGA with analog audio signals from the chassis. Audio output is accessed by connecting the supplied Kramer VGA with audio cables to each VGA port.

FEATURES

- Max. Bandwidth - 450MHz.
- HDTV Compatible.
- Analog Audio Over Breakaway Connector.

TECHNICAL SPECIFICATIONS

PORTS:	2 VGA on 15-pin HD connectors, 2 unbalanced analog audio on 3.5mm mini jack connectors (accessible via C GF/GMAF-30 cables).
BANDWIDTH:	450MHz.
MAXIMUM RANGE:	10m (32ft).
POWER CONSUMPTION:	5.5W.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F) .
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	19cm x 13cm x 2cm (7.5" x 5.1" x 0.8") W, D, H.
PRODUCT WEIGHT:	0.13kg (0.29lbs) approx.
SHIPPING WEIGHT:	0.52kg (1.15lbs) approx.
SAFETY REGULATORY COMPLIANCE:	CE.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.
INCLUDED ACCESSORIES:	2 C-GF/GMAF-30 cables.