



VM-10xl

1:10 Composite Video & Stereo Audio Distribution Amplifier



The **VM-10xl** is a broadcast quality 1:10 distribution amplifier for composite or SDI video signals with unbalanced stereo or balanced mono audio. It provides controls to compensate for signal losses inherent in long cable runs.

FEATURES

- High Bandwidth - 360MHz (-3dB).
- Audio Controls.
- Level (Gain) and EQ (Peaking) Controls.
- Looping Input.
- Selectable Input Signal Termination.
- Video AC/DC Coupling Selection.
- Standard 19" Rack Mount Size - 1U.

TECHNICAL SPECIFICATIONS

INPUTS:	1 composite video with loop, 1Vpp/75Ω with termination switch on BNC connectors; 2 balanced stereo/mono audio with loop, 1Vpp/50kΩ on RCA connectors.
OUTPUTS:	10 composite video, 1Vpp/75Ω on BNC connectors; 10 balanced stereo/mono audio, 1Vpp/50Ω on RCA connectors.
MAX. OUTPUT LEVEL:	Video: 1.6Vpp; Audio: 26.5Vpp.
BANDWIDTH (-3DB):	Video: 360MHz, Audio: 100kHz.
DIFF. GAIN:	0.07%.
DIFF. PHASE:	0.05Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	Video: 77dB, Audio: 87dB.
CONTROLS:	Video level: (-1.2dB to +6dB), EQ. (0dB to +8.1dB); audio level: (0dB to +6dB); balanced/stereo selector switch and audio control enable switch.
COUPLING:	Video: DC/AC; Audio: AC (input), DC (output).
AUDIO THD + NOISE:	0.023%.
AUDIO 2ND HARMONIC:	0.001%.
POWER CONSUMPTION:	230V AC, 50/60Hz, (115V USA), 4.7VA.
INCLUDED ACCESSORIES:	Power cord.
PRODUCT DIMENSIONS:	19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H
PRODUCT WEIGHT:	1.7kg (3.7lbs) approx.
SHIPPING DIMENSIONS:	0.00cm x 0.00cm x 0.00cm (0.00" x 0.00" x 0.00") W, D, H
SHIPPING WEIGHT:	2.5kg (5.6lbs) approx.

