



# KRAMER

## VM-114H2C

2x1:2+2 HDMI & DGKat with RS-232 & IR to HDMI & PoC Long-reach DGKat switchable DA



The VM-114H2C is a high-performance PoC switcher and distribution amplifier for HDMI and DGKat™ twisted pair signals. It reclocks and equalizes one of two selectable input signals (HDMI or DGKat twisted pair) and distributes it to two DGKat twisted pair and two HDMI outputs.

## FEATURES

- **Max. Data Rate** - 6.75Gbps (2.25Gbps per graphic channel) (HDMI), 4.95Gbps (1.65Gbps per graphic channel) (DGKat).
- **HDTV Compatible.**
- **HDCP Compliant.**
- **DGKat™ Signal Integration** - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables.
- **I-EDIDPro™ Kramer Intelligent EDID Processing™** - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- **HDMI Support** - x.v.Color™, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD (only on the TP inputs and outputs).
- **3D Pass-Through.**
- **Kramer Equalization & re-Klocking™ Technology** - Rebuilds the digital signal to travel longer distances.
- **System Range** - Up to 90m (295ft) at 1080i, or up to 30m (98ft) at 1080p on shielded BC-DGKat524 cable. Up to 90m (295ft) at 1080i, or up to 70m (230ft) at 1080p on shielded BC-DGKat623 cable. Up to 100m (330ft) at 1080i or up to 90m (295ft) at 1080p on shielded BC-DGKat7a23 cable.
- **Cable** - Requires STP (shielded twisted pair) cable. For optimum range and performance, use Kramer's BC-DGKat524, BC-DGKat623 or BC-DGKat7a23 cables. Note that the transmission range depends on the signal resolution, source device and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.
- **Active Input & Output LED Indicators.**
- **Compatible Transmitters/Receivers** - Transmitters: PT-571, TP-573, TP-577; Receivers: PT-572, TP-575, TP-576, TP-577.
- **Power Connect™ System** - A single connection to the transmitter or the receiver powers both units when the devices are within 90m (270ft) of each other.
- **Flexible Control Options** - Front panel buttons, RS-232, infrared control sensor, remote included.
- **Desktop Size** - Compact size. 2 units can be rack mounted side-by-side in a 1U rack space with an optional RK-1 adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	1 HDMI connector, 1 DGKat twisted pair on an RJ-45 connector.
OUTPUTS:	2 HDMI connectors, 2 DGKat twisted pairs on RJ-45 connectors.
MAX. DATA RATE::	6.75Gbps (2.25Gbps per graphic channel) (HDMI), 4.95Gbps (1.65Gbps per graphic channel) (DGKat).
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
CONTROLS:	Input select button, EDID select button, panel lock button, RS-232, local and remote IR controls.
INDICATOR LEDS:	IR communication, power, IN 1 (HDMI), IN 2 (CAT 5), OUTPUT 1, 2, 3 and 4.
POWER CONSUMPTION:	12V DC, 910mA.
INCLUDED ACCESSORIES:	Power supply, bracket installation kit, RC-IR3 infrared remote control transmitter.
OPTIONS:	RK-1 19" rack adapter.
PRODUCT DIMENSIONS:	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72" ) W, D, H
PRODUCT WEIGHT:	0.9kg (2.0lbs) approx.
SHIPPING DIMENSIONS:	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83" ) W, D, H
SHIPPING WEIGHT:	1.9kg (4.2lbs) approx.

