



VM-1H4C

1:4 HDMI with RS-232 & IR to PoC Long-reach DGKat DA



The VM-1H4C is a high-quality 1:4 twisted pair distribution amplifier for HDMI signal to PoC Long-reach DGKat signals. The unit receives serial commands and IR signals transparently via the RS-232 port and the TP link. It reclocks and equalizes the input signal and distributes it to four DGKat TP outputs.

FEATURES

- Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- DGKat™ Signal Integration - Kramer's unique technology for converting TMDS as well as control and communication to signals that run over twisted pair cables.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- HDMI Support - x.v.Color™ and uncompressed audio channels, Dolby TrueHD, DTS-HD.
- 3D Pass-Through.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- System Range - Up to 90m (295ft) at 1080i, or up to 30m (98ft) at 1080p on shielded BC-DGKat524 cable. Up to 90m (295ft) at 1080i, or up to 50m (164ft) at 1080p on shielded BC-DGKat623 cable. Up to 100m (330ft) at 1080i or up to 90m (295ft) at 1080p on shielded BC-DGKat7a23 cable.
- Power Connect - The VM-1H4C provides power to the twisted pair receivers when they are within 270ft (90m) of the transmitter.
- Cable - Requires STP (shielded twisted pair) cable. For optimum range and performance, use Kramer's BC-DGKat524, BC-DGKat623 or BC-DGKat7a23 cables. Note that the transmission range depends on the signal resolution, source device and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.
- Active Input & Output LED Indicators.
- Serial Command Handling - Receives serial commands transparently via the RS-232 port and the TP link.
- Desktop Size - Compact size. 2 units can be rack mounted side-by-side in a 1U rack space with an optional RK-1 adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	1 HDMI connector, 1 IR on a 3.5mm mini jack, 1 RS-232 on a 9-pin D-sub connector.
OUTPUTS:	4 twisted pair on RJ-45 connectors.
MAX. DATA RATE:	Supports up to 4.95Gbps (1.65Gbps per graphic channel).
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP.
INDICATOR LEDS:	Power, INPUT, OUTPUT 1, 2, 3 and 4.
POWER CONSUMPTION:	12V DC, 2A.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-1 19" rack adapter.
PRODUCT DIMENSIONS:	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H
PRODUCT WEIGHT:	0.0kg (0.0lbs) approx.
SHIPPING DIMENSIONS:	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H
SHIPPING WEIGHT:	1.9kg (4.2lbs) approx.

