



## VM-24HDCP

2x1:4 DVI (HDCP) selectable DA

---



The VM-24HDCP is a high-performance distribution amplifier for DVI signals. The unit reclocks and equalizes one of two input signals and distributes it to four identical outputs.

### FEATURES

---

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support - HDMI Compressed Audio Channels.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for DVI systems.
- Control - Front panel & IR switching.
- Worldwide Power Supply - 100-240V AC.
- Standard 19" Rack Mount Size - 1U. Rack "ears" included.

TECHNICAL SPECIFICATIONS

INPUTS:	2 DVI, 1.2Vpp on a DVI Molex 24-pin (F) connector; DDC signal 5Vpp (TTL).
OUTPUTS:	4 DVI, 1.2Vpp on DVI Molex 24-pin (F) connectors; DDC signal 5Vpp (TTL).
MAX. DATA RATE:	6.75Gbps (2.25Gbps per graphic channel).
CONTROLS:	EDID SELECT, EDID READ, IN 1, IN 2 buttons, RS-232, IR.
INDICATOR LEDES:	OUTPUT STATUS LEDES.
POWER CONSUMPTION:	100–240V AC, 50/60Hz 17VA.
INCLUDED ACCESSORIES:	Power cord, rack "ears", null-modem adapter, Windows®-based control software, infrared remote control transmitter.
PRODUCT DIMENSIONS:	19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H
PRODUCT WEIGHT:	1.5kg (3.3lbs) approx.
SHIPPING DIMENSIONS:	55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21" ) W, D, H
SHIPPING WEIGHT:	2.3kg (5.1lbs) approx.

