



VM-3AN

1:3 Balanced Stereo Audio Distribution Amplifier



The **VM-3AN** is a high-performance distribution amplifier for balanced stereo audio signals. The unit takes one stereo input and distributes the signal to three identical outputs.

FEATURES

- S/N Ratio - 90dB.
- L & R Level (Gain) Controls.

TECHNICAL SPECIFICATIONS

INPUT:	1 balanced stereo audio on a 5-pin terminal block.
OUTPUTS:	3 balanced stereo audio on 5-pin terminal blocks.
MAX. OUTPUT LEVEL:	Audio: 18.5Vpp.
BANDWIDTH (-3DB):	>100 kHz.
S/N RATIO:	90dB @1kHz.
CONTROL:	Output level control:-77 to +6dB, R+/-, L+/- channels.
AUDIO THD + NOISE:	0.008%.
AUDIO 2D HARMONIC:	0.001%.
POWER CONSUMPTION:	12V DC, 89mA.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-3T 19" rack adapter.
PRODUCT DIMENSIONS:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx.
SHIPPING DIMENSIONS:	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx.

