



VM-4HC

1:4 HDMI Distribution Amplifier



The **VM-4HC** is a distribution amplifier for HDMI signals. It reclocks and equalizes the signal and distributes it to four identical outputs.

FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- EDID Acquisition - Default, single output or all connected outputs (auto-mix).
- HDMI Support - Deep Color, x.v.Color™, up to 7.1 Uncompressed Audio Channels.
- 3D Pass Thru.
- Active Input & Output LED Indicators.

TECHNICAL SPECIFICATIONS

INPUT:	1 HDMI connector.
OUTPUTS:	4 HDMI connectors.
MAX. DATA RATE:	6.75Gbps (2.25Gbps per graphic channel).
COMPLIANCE WITH HDMI STANDARD:	HDMI and HDCP.
CONTROLS:	SELECT and READ buttons for selecting and storing EDID information.
INDICATOR LEDS:	OUTPUTS 1 to 4 and power LEDs.
POWER CONSUMPTION:	5V DC, 1.1A.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-1 19" rack adapter.
PRODUCT DIMENSIONS:	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H
PRODUCT WEIGHT:	0.6kg (1.4lbs) approx.
SHIPPING DIMENSIONS:	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H
SHIPPING WEIGHT:	1.2kg (2.6lbs) approx.

