



## VP-427A

HDBaseT to HDMI & Audio ProScale™ Receiver/Scaler



The Kramer VP-427A is a receiver/scaler for HDBaseT twisted pair, HDMI, bidirectional RS-232 and IR signals. The unit receives an HDBaseT signal that it converts to HDMI, IR and RS-232 signals. It up- or down-scales the picture to match the resolution of the HDMI monitor. It includes a simultaneous analog audio output of the embedded HDMI audio.

### FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- Bidirectional RS-232 Port - For embedding/de-embedding control commands in the HDBaseT data stream.
- Infrared Input and Output Ports - For controlling devices over the HDBaseT data stream.
- System Range - Up to 70m (230ft).
- Embedded Audio - Support for LPCM 2CH.
- Analog Audio Output - Includes a simultaneous unbalanced stereo audio output of the embedded HDMI audio.
- Constant Output Sync - Even when the input video signal is lost or interrupted.
- ProcAmp Control - Contrast, brightness, fine tune & R, G, B level/gain.
- On-Screen Display (OSD) - For easy setup and adjustment, accessible via the front-panel buttons.
- Non-Volatile Memory - Saves final settings.
- Freeze Button.
- USB Port - For upgrading firmware.

TECHNICAL SPECIFICATIONS

INPUTS:	1 HDBaseT twisted pair on an RJ-45 connector, 1 IR on a 3.5mm mini jack.
OUTPUTS:	1 HDMI connector, 1 IR on a 3.5mm mini jack, 1 unbalanced stereo audio on a 3.5mm mini jack.
PORTS:	1 bidirectional RS-232 port on a 9-pin D-sub connector.
OUTPUT RESOLUTIONS:	Native, 480p, 570p, 720p, 1080i, 1080p, 640x480, 800x600, 1024x768, 1280x800, 1280x1084, 1360x768, 1400x1050, 1440x900, 1600x1200, 1680x1050, 1920x1200.
OUTPUT REFRESH RATE:	60Hz for computer graphics resolutions, 50/60Hz for HDTV resolutions.
LATENCY:	30ms approx.
VIDEO COLOR DEPTH:	Input: 8/10/12-bit, output: 8-bit.
EMBEDDED AUDIO:	Supports LPCM 2CH.
RS-232 BAUDRATE:	115200bps max.
CONTROLS:	Front panel buttons, 1 USB for programming.
INDICATORS:	ON LED.
POWER CONSUMPTION:	5V DC, 1.5A.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-T2B 19" rack adapter.
PRODUCT DIMENSIONS:	18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00" ) W, D, H
PRODUCT WEIGHT:	0.5kg (1.0lbs) approx.
SHIPPING DIMENSIONS:	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05" ) W, D, H
SHIPPING WEIGHT:	1.0kg (2.2lbs) approx.

