



VP-4xl

1:4 Computer Graphics Video Distribution Amplifier



Compatible with HDTV component video signals when used with a breakout cable such as the Kramer C-GM/3RVF.



The **VP-4xl** is a high-performance distribution amplifier for computer graphics video signals with resolutions ranging from VGA through UXGA and higher. The unit takes one input, provides correct buffering and isolation, and distributes the signal to four identical outputs.

FEATURES

- High Bandwidth - 375MHz (-3dB).
- HDTV Compatible.
- EQ (Peaking) Control.
- ID Bit Control.
- Desktop Size - Compact size. Two units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 adapter.

TECHNICAL SPECIFICATIONS

INPUT:	1 VGA/UXGA input on a 15-pin HD (F) connector.
OUTPUT:	4 VGA/UXGA on 15-pin HD (F) connectors.
BANDWIDTH (-3DB):	375MHz.
MAX. OUTPUT LEVEL:	1.9Vpp.
DIFF. GAIN:	0.12%.
DIFF. PHASE:	0.28Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	73.7dB.
CONTROLS:	EQ: 0 to 6.6dB @50MHz.
COUPLING:	DC.
POWER CONSUMPTION:	100-240V AC, 50/60Hz, 4.3VA.
INCLUDED ACCESSORIES:	Power cable.
OPTIONS:	RK-1 19" rack adapter.
PRODUCT DIMENSIONS:	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H
PRODUCT WEIGHT:	1.2kg (2.6lbs) approx.
SHIPPING DIMENSIONS:	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H
SHIPPING WEIGHT:	1.7kg (3.8lbs) approx.

