



VS-211H2

2x1 4K HDR HDCP 2.2 HDMI Auto Switcher



VS-211H2 is a high-performance automatic switcher for 4K HDR, HDCP 2.2, HDMI 2.0 video signals. Offering priority and last-connected switching options, it automatically switches according to the selected switching scheme based on active video signal detection.

FEATURES

- Max. Data Rate - 17.82Gbps (5.94Gbps per data channel).
- Max. Resolution - 4K@60Hz (4:4:4).
- Kramer Equalization and re-Klocking Technology.
- HDR Support.
- HDTV Compatible.
- HDMI 2.0 & HDCP 2.2 Compliant.
- 3D Pass-Through.

TECHNICAL SPECIFICATIONS

INPUTS:	2 HDMI connectors.
OUTPUTS:	1 HDMI connector.
MAX. DATA RATE	17.82GBPS (5.94Gbps per graphic channel).
MAX. RESOLUTION	4K@60Hz (4:4:4).
STANDARDS COMPLIANCE	HDR10, HDCP 2.2 (does not support conversion to HDCP 1.4), HDMI 2.0.
CONTROLS:	Status/priority DIP-switches, contact closure remote control.
REGULATORY CERTIFICATION:	EMC EN 55032;IEC 60950-1(ed.2);IEC 60950-1(ed.2)am1;IEC 60950-1(ed.2) am2.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
POWER CONSUMPTION:	5V DC, 400mA.
INCLUDED ACCESSORIES:	Power supply 5.2V DC/4A desktop.
OPTIONS:	RK-3T 19" rack adapter.
PRODUCT DIMENSIONS:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx.
SHIPPING DIMENSIONS:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.6kg (1.4lbs) approx.

