



VS-311H

3x1 HDMI, Stereo & S/PDIF Audio Standby Switcher



The VS-311H is a high-performance switcher for HDMI video and balanced, unbalanced and S/PDIF audio signals. When configured as a standby switcher, it switches to a selectable secondary input upon loss of the primary input.

FEATURES

- Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel).
- HDTV Compatible.
- HDCP & HDMI Compliant.
- Flexible Control Options - Automatic (standby), RS-232, Ethernet, contact closure & IR (included).
- Input Priority - Selectable via DIP-switches.
- Desktop Size - Compact size. 2 units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 adapter.

TECHNICAL SPECIFICATIONS

INPUTS:	3 HDMI connectors, 3 S/PDIF digital audio on RCA connectors, 3 unbalanced stereo audio +4dBu on 3.5mm mini jacks.
OUTPUTS:	1 HDMI connector, 1 S/PDIF digital audio on an RCA connector, 1 unbalanced stereo audio +4dBu on a 3.5mm mini jack, 1 balanced stereo audio on a 5-pin detachable terminal block.
DATA RATE:	6.75Gbps (2.25Gbps per graphic channel).
POWER CONSUMPTION:	12V DC, 380mA.
CONTROLS:	Front panel buttons, infrared remote control transmitter, RS-232, Ethernet.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-1 19" rack adapter.
PRODUCT DIMENSIONS:	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H
PRODUCT WEIGHT:	0.0kg (0.0lbs) approx.
SHIPPING DIMENSIONS:	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H
SHIPPING WEIGHT:	1.3kg (3.0lbs) approx.

