



VS-33Vxl

3x1 Composite Video Switcher



The **VS-33Vxl** is a high-performance switcher for composite video signals. Switching during the vertical interval ensures glitch-free switching with genlocked sources.

FEATURES

- Bandwidth - 46MHz (-3dB).
- Vertical Interval Switching - Genlocks to input 1.
- Contact Closure Remote Switching Capability.

TECHNICAL SPECIFICATIONS

INPUTS:	3 composite video, 1Vpp/75Ω on BNC connectors.
OUTPUT:	1 composite video, 1Vpp/75Ω on a BNC connector.
MAX. VIDEO OUTPUT:	1.8Vpp/75Ω.
VIDEO BANDWIDTH (-3DB):	46MHz.
DIFF. GAIN:	1.25%.
DIFF. PHASE:	0.5Deg.
K-FACTOR:	<0.05%.
VIDEO S/N RATIO:	73dB.
SWITCHING:	Vertical interval.
CROSSTALK:	-44dB @5MHz.
POWER CONSUMPTION:	5V DC, 22mA.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-3T 19" rack adapter.
PRODUCT DIMENSIONS:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.5lbs) approx.
SHIPPING DIMENSIONS:	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H
SHIPPING WEIGHT:	0.6kg (1.2lbs) approx.

