



## VS-88A

8x8 Balanced Stereo Audio Matrix Switcher

---



The **VS-88A** is a high-performance matrix switcher for balanced stereo audio signals. It can route any or all inputs to any or all outputs simultaneously.

### FEATURES

---

- S/N Ratio - 84dB unweighted (1Vpp).
- Control - Front panel, RS-232 (K-Router™ Windows®-based Kramer software is included), RS-485.
- Take Button - Executes multiple switches all at once.
- Memory Locations - Stores multiple switches as presets to be recalled and executed when needed.
- Worldwide Power Supply - 100-240V AC.

TECHNICAL SPECIFICATIONS

INPUTS:	8 balanced stereo audio, +4dBu/33kΩ on detachable terminal blocks.
OUTPUTS:	8 balanced stereo audio, +4dBu/50Ω (20Vpp max) on detachable terminal blocks.
AUDIO BANDWIDTH (-3DB):	100kHz.
AUDIO S/N:	84dB unweighted (1Vpp).
CONTROL:	22 front panel buttons, RS-232 and RS-485 control interface.
AUDIO THD:	0.025% (1Vpp, 1kHz).
2ND HARMONIC:	0.013%.
MAX. AUDIO:	>20dBu.
INDICATORS:	8-character display on the front panel.
POWER CONSUMPTION:	115/230V AC, 50/60Hz, 16VA max.
INCLUDED ACCESSORIES:	Power cord.
PRODUCT DIMENSIONS:	19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H
PRODUCT WEIGHT:	3.0kg (6.6lbs) approx.
SHIPPING DIMENSIONS:	55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21" ) W, D, H
SHIPPING WEIGHT:	3.8kg (8.3lbs) approx.

