



SID-X2N

4-Input Multi-Format Video over HDBaseT Transmitter & Step-In Commander



The SID-X2N is an HDBaseT twisted pair transmitter and step-in commander for computer graphics video, HDMI, DVI, DisplayPort and unbalanced stereo audio signals.

FEATURES

- **Max. Data Rate** - 6.75Gbps (up to 1080p @60Hz 36bpp) in normal mode; up to 4.95Gbps (up to 1080p @60Hz 24bpp) in ultra mode.
- **HDTV Compatible.**
- **HDCP Compliant** - Works with sources that support HDCP repeater mode.
- **HDMI Support** - Deep Color, x.v.Color™ and 3D.
- **I-EDIDPro™ Kramer Intelligent EDID Processing™** - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- **Data Equalization and Reclocking.**
- **Input Signal Detection** - Based on video clock presence.
- **Automatic Input Selection** - Based on manual selection or last connected input.
- **Automatic Analog Audio Detection and Embedding.**
- **Local Balanced Audio De-Embedding.**
- **Support for Digital Audio Formats.**
- **Lockable EDID.**
- **System Range** - Up to 130m (430ft) at normal mode (2K), up to 100m at normal mode (4K); up to 180m (590ft) ultra mode (1080p @60Hz @24bpp) when using BC-HDKat6a cables.
- **Local Step-In Switching** - Button & contact closure.
- **Power Supply** - Requires independent power supply.

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|---|
| INPUTS: | 1 HDMI on an HDMI connector, 1 DP on a DisplayPort connector, 1 DVI-D on a DVI-I connector 1 VGA on a 15-pin HD (F) connector, 1 unbalanced stereo audio on a 3.5mm mini jack. |
| OUTPUTS: | 1 HDBaseT TP on an RJ-45, 1 unbalanced stereo audio in a 3.5mm mini jack. |
| PORTS: | 1 RS-232 3-pin terminal block for programming. |
| CONTROLS: | Front panel buttons, remote step-in switch, remote input selection switches. |
| ANALOG AUDIO INPUT: | Maximum level – 3Vpp. |
| REMOTE LED IMPEDANCE: | 5V, 300Ω approx. |
| STANDARDS: | HDMI with x.v.Color™ and 3D; HDCP: works with sources that support HDCP repeater mode. |
| MAXIMUM DATA RATE: | 6.75Gbps (up to 1080p @60Hz 36bpp) in normal mode; up to 4.95Gbps (up to 1080p @60Hz 24bpp) in extended mode. |
| MAXIMUM TRANSMISSION DISTANCE: | 180m (590ft) up to 1080p @60Hz @24bpp in extended mode; 130m (430ft) up to 1080p @60 @36bpp in normal mode. |
| POWER CONSUMPTION: | 12V DC, 950mA. |
| COMPLIANCE STANDARDS: | CE, UL. |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F). |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F). |
| HUMIDITY: | 10% to 90%, RHL non-condensing. |
| COOLING: | Convection, vents. |
| ENCLOSURE TYPE: | Aluminium. |
| INCLUDED ACCESSORIES: | Power adapter. |
| OPTIONS: | RK-T2B 19" rack adapter, RTBUS-12, RTBUS-22, SID-X1NBP Kit (substitute black top plate for the SID-X2N to blend in with the color of the modular TBUS-10xl). |
| PRODUCT DIMENSIONS: | 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H |
| PRODUCT WEIGHT: | 0.5kg (1.0lbs) approx. |
| SHIPPING DIMENSIONS: | 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H |
| SHIPPING WEIGHT: | 1.4kg (3.1lbs) approx. |

